

Model Name / No.		P3- 60	P3 -132S
Operational Method		Roller-Type	
Max. Cutting Width		590 mm(23.23 in.)	1300 mm(51.18 in.)
Max. Media Loading Width		719 mm(28.3 in.)	1470 mm(57.87 in.)
Min. Media Loading Width		50 mm(1.97 in.)	
Acceptable Material Thickness		0.8 mm (0.03 in.)	
Number of Pinch Rollers		2	4
Drive		DC Servo Control	
Cutting Force		400g	
Max. Cutting Speed (Diagonal)		Up to 600 mm /sec (24 ips)	
Offset		0-1.0 mm (with an increase of 0.025 mm)	
Mechanical Resolution		0.009 mm (0.00035")	
Software Resolution		0.025 mm (0.00098")	
Distance Accuracy		±0.254 mm or ±0.1% of move, whichever is greater	
Memory Size		4 MB	
Interfaces		USB 2.0 (Full Speed) & Serial (RS-232C)	
Type of Command		HP-GL, HP-GL/2	
Configurable Origin		Yes	
Curve & Arc Smoothing		Yes	
Test Cut Capability		Yes	
Repeat Function		Yes	
Copy Function		Yes	
Tangential Mode		Yes	
Overcut Capability		Yes	
Pause and Move		Yes	
Control Panel		LCM (20 digits X 2 lines), 14 Keys , 1 power LED	
Dimension (H x W x D)		220 x 879 x 258 mm 8.76 x 34.61 x 10.16 in.	1065 x 1632 x 620 mm (Stand Including) 41.93 x 64.25 x 24.41 in.
Net Weight		13 kg / 28.6 lb	53 kg / 116.4 lb
Power Supply		AC 100-240V, 50~60 Hz (auto switching)	
Operation Environment	Temperature	15°-30°C (60°-86°F)	
	Humidity	25%-75%	